

PAT-NO: JP361111333A
DOCUMENT-IDENTIFIER: JP 61111333 A
TITLE: PRODUCTION OF WET FRICTION MATERIAL COMPOSITION
PUBN-DATE: May 29, 1986

INVENTOR-INFORMATION:

NAME	COUNTRY
USUI, SUSUMU	
NAKAZAWA, SHIRO	

ASSIGNEE-INFORMATION:

NAME	COUNTRY
TOSHIBA TUNGALOY CO LTD	N/A

APPL-NO: JP59232222
APPL-DATE: November 2, 1984

INT-CL (IPC): C08 J 005/14 , F16 D 069/00

US-CL-CURRENT: 508/591

ABSTRACT:

PURPOSE: To produce the titled composition excellent in elasticity, seizing resistance, durability, a coefficient of friction, etc., by mixing a lubricant, a mineral substance, a friction modifier and a fiber all of which are coated or impregnated with a rubber material with a specified binder.

CONSTITUTION: A lubricant component (B) such as graphite, MoS₂ or lead, a mineral substance (C) comprising a hard material of a Mohs, hardness ≥ 4 , a friction modifier (D) such as BaSO₄, CaCO₃ or MgCO₃ or a fiber (E) such as pulp fiber, carbon fiber or aromatic polyamide fiber are coated or impregnated with a rubber material (A) selected from among nitrile rubber, acrylonitrile/butadiene copolymer rubber, styrene/butadiene copolymer rubber, fluororubber, etc. At least 5wt% at least one component selected from among 70wt% or below component B, 30wt% or below component C, 25wt% or below component D and 80wt% or below component E is mixed with 5-50wt% heat-resistant binder (F) such as phenolic resin or epoxy resin so that the resulting composition may contain 2-80wt% component A.

COPYRIGHT: (C)1986,JPO&Japio